

# HF 400 II ELITE *Full digital*

- **CONNECTIVITY WITH ANY DIRECT DIGITAL SYSTEM TO OUR RADIOLOGICAL**
- **COMPONENTS AND CERTIFICATIONS UPDATED TO 2024**
- **ROTATING HEAD AND MOVING COLUMN ARE FUNCTIONAL FOR DIAGNOSIS ON EXOTIC ANIMALS AND FOR ORTHOPEDICS**

thanks to their dynamics in movement, which allows X-rays to be taken at different angles for the different projections that need to be made, making the operator's work easier and faster.



**EIZO MEDICAL MONITOR**  
with 7m video cable

Monitor  
21" touch screen

**NEMO SPACE VET  
INTERFACE**  
for remote support  
+  
interconnection

**TECHNIQUE  
3 POINTS**

kV - mA - Time

**TECHNIQUE  
2 POINTS**

kV - mAs

Head rotation  
+/- 90°



Cleat rope ties

Variable column  
for lateral projections



Steel bucky tray



Removable x-ray grid

**"floor track"  
system**

## HF 400 II ELITE *Full digital* | Variable column, rotating head and floor track

X- RAY GENERATOR	X-RAY TUBE	POWER	OPTIONAL
Monobloc	X-ray tube with rotating anode	Standard Voltage 230/240 V ± 10% 50-60 Hz	X-ray hand switch
Max Power 30 kW	Focal spot 0,6-1,3 mm	Power consumption < 1A	Removable anti-scatter 43x43 cm 10 lines/inch
Max Voltage 125 kV	Anode angle 15°	<b>DIMENSIONS</b>	Different colors available on request
Max Power Supply 400 mA	Heat capacity from 80KJ - 107 KHU	L 150 x L 98 x H 200 cm	
Selection of exposure time from 0,002 to 1 sec.	<b>ANTI-SCATTER GRID</b>	<b>COLLIMATOR</b>	
X-ray foot switch in 2 steps, cable 6 mt long	Removable anti-scatter grid 35 x 43 cm 103 lines/inch	Manual setting field	
Leakage radiation less than 3,5 µ SV/h in accordance with IEC EN 60601-1-3		Variable range at 43x43 cm @ 100 cm SID	
		High intensity white LED lamp 160-220 lux at 100cm with automatic switch	

TABLE	EXAMVUE DUO SOFTWARE	X-RAY DETECTOR	
		WIRELESS	WIRED
Patient support table 4 ways with mechanical brakes	Simple and intuitive software for patient and owner registration, anatomical part selection and veterinary-specific measurements with Tutorial	<b>Scintillator</b> Direct Deposit CsI:TI	<b>Scintillator</b> Direct Deposit CsI:TI
Max weight capacity for patient support table 100 kg	Setting patient parameters in thickness	<b>Active Area</b> 433.5 x 433.5 mm	<b>Active Area</b> 430 x 430 mm
Table absorption thickness 5mm 0,8mm	Anatomical parts programmed and reprogrammable on request to technical service	<b>Pixel pitch</b> 154 µm	<b>Pixel pitch</b> 140 µm
Variable film focus distance	One of our highlights is a professional positioning guide that assists veterinarians during examinations, ensuring high quality images with anatomical precision	<b>Image Acquisition Time</b> 2-3 sec (wired) 4-5 sec (wireless)	<b>Image Acquisition Time</b> 2-4 sec
Standard table top length: 200 cm	With the 'Full Digital' line, veterinarians have the possibility of conducting the entire examination process in a single interface, allowing a smoother workflow and avoiding the need to switch from one phase to another		
21" full HD touch screen for greater operator efficiency in carrying out the work process	Second Eizo medical monitor 24"		